



# PRODUCT DATA SHEET

[www.btm.co](http://www.btm.co)

Bituminous Waterproofing Membranes Co.  
Kemalpaşa Org. San. Bölgesi Mah. Gazi Bulvarı. No:  
152 Kemalpaşa / İZMİR / TURKEY  
Tel: +90 0232 877 04 02 (8 line)  
Fax: +90 0232 877 04 10

## BTM DRAINAGE

### 2\*20m HDPE MEMBRANE 400

Document number : PDS-152-0

Publication Date: 31.03.2014 Revision date : -

<b>PRODUCT DESCRIPTION</b>	HDPE Dimpled Membrane			
<b>USAGE</b>	Protection and drainage sheet with extremely high loadability; designed for use to protect foundation waterproofing, under roofing and flooring, under driveways, access roads for fire brigades, parking areas, etc.			
<b>STORAGE</b>	Should be stored away from direct sunlight			
<b>ECOLOGICAL DATA</b>	Does not contain toxic substances harmful to the environment			
<b>TEST</b>	<b>METHOD</b>	<b>UNIT</b>	<b>TOLERANCE</b>	<b>VALUES</b>
WIDTH / LENGTH	TS EN 1849-1	m	-	2m * 20m
THICKNESS	TS EN ISO 9863-1	mm	±1%	7,5
COLOR	-	-	-	Black
UNIT OF WEIGHT	TS EN ISO 9864	gr/m <sup>2</sup>	±5%	400
COMPRESSIVE STRENGTH	EN ISO 25619-2	kN/m <sup>2</sup>	-	approx.150
TENSILE STRENGTH (Longitudinal)	TS EN 12311-1	N/50mm	min.	200
ELONGATION at BREAK (Longitudinal)	TS EN 12311-1	%	min.	25
TENSILE STRENGTH (Transverse)	TS EN 12311-1	N/50mm	min.	200
ELONGATION at BREAK (Transverse)	TS EN 12311-1	%	min.	25
MATERIAL	-	-	-	PE - HD

