



www.btm.co

Bituminous Waterproofing Membranes Co.
Kemalpaşa Org. San. Bölgesi Mah. Gazi Bulvarı. No:
152 Kemalpaşa / İZMİR / TURKEY
Tel:+90 0232 877 04 02 (8 line)
Fax: +90 0232 877 04 10

PRODUCT DATA SHEET



TS EN 13707

ELASTOSELF MD KUMLU

Document number :PDS-146-05
Publication Date :05th,Jan.2009 Revision date : 23th.May.2018

PRODUCT DESCRIPTION	Elastomeric modified bituminous waterproofing membrane.			
USAGE	Used for water profing of terraces and roofs in foundation curtains.			
APPLICATION METHOD	Self-adhesive			
TOP SURFACE	Fine sand			
BOTTOM SURFACE	Siliconized film			
REINFORCEMENT TYPE	Polyester			
STORAGE	Rolls to be stored upright and away from heat.			
ECOLOGICAL DATA	Can be used in natural atmosphere			
TEST	METHOD	UNIT	TOLERANCE	VALUES
Visible defects	TS EN 1850-1	-	-	NONE
Length	TS EN 1848-1	m	-0,03	20
Width	TS EN 1848-1	m	-0,02	1
Thickness	TS EN 1849-1	mm	min.	1,5
Tensile Strength (Longitudinal)	TS EN 12311-1	N/50mm	-%0 ; '+%30	500
Elongation at break (Longitudinal)	TS EN 12311-1	%	(-0 ; +20)	30
Tensile Strength (Transverse)	TS EN 12311-1	N/50mm	-%0 ; '+%30	300
Elongation at break (Transverse)	TS EN 12311-1	%	(-0 ; +20)	30
Flexibility at low temperature	TS EN 1109 (top surface)	°C	min.	-15
	TS EN 1109 (bottom surface)	°C	min.	-15
Reaction to fire	TS EN 13501-1	class	-	E

NPD = (No performance defined)

* For information and advice on the safe handling,storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet

The manufacturer serves the right to modify, at any time, the characteristics of its products

BF/14-17-0