



www.btm.co

Bituminous Waterproofing Membranes Co.
Kemalpaşa Org. San. Bölgesi Mah. Gazi Bulvarı. No:
152 Kemalpaşa / İZMİR /TURKEY
Tel:+90 0232 877 04 02 (8 line)
Fax: +90 0232 877 04 10

PRODUCT DATA SHEET

ALS-100 ALUSOL

Document number :PDS-001-0
Publication Date :01th,Oct.2010 Revision date : -

| PRODUCT DESCRIPTION | Solvent based-cold applied bituminous waterproofing liquid containin reflective aluminium | | | |
|--|---|--------------------|------------------|---------------|
| USAGE | On all bituminous coating and isolated surfaces which are required to be protected against UV radiation , In protecting the surfaces of metallic or cast elements such as tanks and pipes against corrosion (preferably single coat after application of BTM Elastosol)- Type 1 | | | |
| APPLICATION METHOD | Applied with brush. Please refer to application booklet. | | | |
| STORAGE | Pails stored away from direct sunlight | | | |
| ECOLOGICAL DATA | Can be used in natural atmosphere | | | |
| TEST | METHOD | UNIT | TOLERANCE | VALUES |
| Viscosity at 25 ^o C | TS 103 | cP | - | 25 - 150 |
| Water Content | TS 103 | % | - | 0 |
| Distillation at 0-225 °C | TS 103 | % | Min. | 35 |
| Distillation at 225-360 °C | TS 103 | % | Max. | 65 |
| Residue Penetration at 25 ^o C (100 gr, 5s) | TS 103 | dmm | ±15 | 35 |
| Matter soluble in trichloroethylene | TS 103 | % | Min. | 99 |
| Density | TS 103 | gr/cm ³ | ±0,03 | 0,095 |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

NPD = (No performance defined)
* For information and advice on the safe handling,storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet

The manufacturer serves the right to modify, at any time, the characteristics of its products BF/14-17-0