

PRODUCT DATA SHEET

www.btm.co

Bituminous Waterproofing Membranes Co.
Kemalpasa Org. San. Bölgesi Mah. Gazi Bulvarı. No:
152 Kemalpaşa / İZMİR /TURKEY
Tel:+90 0232 877 04 02 (8 line)
Fax: +90 0232 877 04 10

ELT-400 ELASTOPAST

(Bituminous Mastic Sealant)

Document number :PDS-007-0

Publication Date : 05th, Jan. 2009 Revision date : -				
PRODUCT DESCRIPTION	Cold applied rubber-modified bitumen joint sealer or adhesive			
USAGE	Sealing leaks and making repairs, fixing roofing felt overlaps and many other roofing, plumbing and waterproofing tasks for buildings. For waterproofing cracks and joints in dams and bridges.Waterpoof finishing of overlaps, connetctions and joints of roof			
APPLICATION METHOD	Oil products can dissolve the bitumen. So, usage of these components with Elastopast is not recomended. Elastopast can be applied with a handgun or a a compressed airgun.			
STORAGE	Should not be stored in direct sunlight or a near a source of heat.			
ECOLOGICAL DATA	Can be used in natural atmosphere			
TEST	METHOD	UNIT	TOLERANCE	VALUES
Specific Gravity	-	gr/cm ³	Min.	1,2
Resistance to flow at elevated temperature (70°C with 90° angle)	-	mm	-	No flow after 24 hours
Surface adhesion	-	-	-	pass
Curing time (depends on substrate)	-	days	-	1 -10
NPD = (No performance defined)		hall askas ka ki i i i	and an and Material Co.	to Data Chart

* For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet